



Hydraulic crimping tools are professional tool crimp for copper & aluminium cable lugs in hexagonal shape.

Available different type of crimping tools with suitable crimping dies.

Punch driver kit is enable to make holes & square cutouts on the enclosures..

ZUPPER - Hong Kong  **ZUPPER**

Ordering Information

Order No	Model No	Product	Crimping Range	Pressure Tons
133305	YYQ-120	Hydraulic Crimping Tool	6-120 mm ²	60KN
133320	YQK-240	Hydraulic Crimping Tool	16-240 mm ²	70KN
133325	YQK-300	Hydraulic Crimping Tool	10-300 mm ²	70KN
133330	HZ-400	Hydraulic Crimping Tool	16-400 mm ²	120KN
133340	FHT-400U	Hydraulic Crimping Tool	16-400 mm ²	120KN
133400	SYK-8B	Punch driver kit	22.5-61.5 mm	100KN
133351	CP-180B	Hydraulic pump		
133350	CP-390	Hydraulic pump		

Technical Details

YYQ-120



Crimping range:	Cu 10-120 mm ²
Crimping force:	60KN
Crimping type:	Hexagon crimping
Stroke:	13mm

Length:	approx.415mm
Weight:	approx.2.8kg
Package:	Plastic box
Weight of box:	approx.0.9kg
ACCESSORIES:	
Crimping dies:	10, 16, 25, 35, 50, 70, 95, 120 mm ²
Sealing O-ring:	one set

YQK-240



- Hydraulic crimping tool is a professional tool for crimping copper and aluminum lugs with different types, a wide range of crimping dies from 4 mm² to 1000 mm² to suit for different size demand. The main crimping shape is hexagonal, special shape design is provided.

Crimping range:	Cu 16-240 mm ²
Crimping force:	70KN
Crimping type:	Hexagon crimping
Stroke:	18mm
Length:	approx.475mm
Weight:	approx.3.6kg
Package:	Plastic box
Weight of box:	approx.1.80kg
ACCESSORIES:	
Crimping dies:	16, 25, 35, 50, 70, 95, 120, 150, 240 mm ²
Sealing O-ring:	one set

YQK-300

Crimping range:	Cu 10-300 mm ²
Crimping force:	70KN
Crimping type:	Hexagon crimping
Stroke:	18mm
Length:	approx.475mm
Weight:	approx.3.6kg
Package:	Plastic box
Weight of box:	approx.1.80kg
ACCESSORIES:	
Crimping dies:	10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300 mm ²
Sealing O-ring:	one set



HZ-400

- The tool features with C type head interchangeable dies.
- For easy operation and comfort the operator can make the tool head fully rotated tool 360°.
- A double speed action reflected by a fast advancing speed for rapid approach of the crimping die the connector and a slower more powerful speed for crimping.
- The built-in safety value will by pass the oil supply when the maximum pressure is reached, automatically pressure release. Manual retract after crimping.

Crimping range:	Cu 16-400 mm ²
Crimping force:	120KN
Stroke:	42mm
Length:	540mm
Weight:	6.3kg
Package:	Steel case
ACCESSORIES:	
Crimping dies:	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400 mm ²



FHT-400U

- Split hydraulic crimping head can work with hydraulic pump. It is suit for crimping big size of lugs.
- It is suitable for outside and inside project of the distributor house, the special tools for all kinds of connecting and building over head cable.

Crimping range: Cu 16-400 mm²

Crimping force: 120KN

Working pressure: 700bar.Max

Stroke: 20mm

Weight: approx.3.9kg

Package: Steel case

ACCESSORIES:

Crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400 mm²

Sealing O-ring: one set



SYK-8B

- The finished distributor, on-off case and plate can change the specification at any time.
- We can make the tools according to customer's requirement, quick delivery.
- When order rectangle and square tools, please measure the correct dimension.

Punching range: $\Phi 22.5$ - $\Phi 61.5$ mm in the 3.5 mm mild steel.

Punching force: 100KN

Stroke: 25mm

Weight: 5.6kg

Package: Steel case

Weight of the box: 3.0kgs

ACCESSORIES:

Round Knockout punches Type D: 22.5, 28.3, 34.6, 43.2, 61.5 mm

7/16"x3/4" Draw Stud:1pc

3/4"x3/4" Draw Stud:1pc

Spacer:1pc

Sealing kit:1set

Plastic box:1pc



CP-180B

- Hydraulic operated pump to drive crimping head, cutting heads and punching head including high pressure hose and coupler plug.
- PT3/8" screw thread, the oil number is shell Tellus T 15, which must be changed every half year.

Type	hand
Max output pressure	70MPa
Output of the oil	1.5cc
Capacity of oil:	185cc
Direction of piston	single
Weight:	approx.6kg
Measurement (LxWxH)	350x120x130mm



CP-390

- Hydraulic operated pump to drive crimping head, cutting heads and punching head including high pressure hose and coupler plug.
- PT3/8" screw thread, the oil number is shell Tellus T 15, which must be changed every half year.

Type	hand	
Max output pressure	Low pressure	2MPa
	High pressure	70MPa
Output of the oil	Low pressure	4cc
	High pressure	1cc
Capacity of oil:	390cc	
Direction of piston	double	
Weight:	approx.4.6kg	
Measurement (LxWxH)	400x105x155mm	

