

8PK-ST1520



- 3 1/2 digit 1999 counts.
- Capable of measuring earth voltage.
- 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test.
- Extra function: data hold, auto power off, low battery, over range indication.
- Safety standard: IEC-1010(EN61010), installation Category III.
- Measurement: Earth Resistance by constant current.
- System: Invertor.820Hz, 2mA approx.
- Earth Voltage: 0~200V AC, 40~500Hz.
- Earth Resistance Range(Resolution): 0~20Ω(0.01Ω); 0~200Ω(0.4Ω), 0~2000Ω(1.0Ω).
- Accuracy: Earth voltage $\pm(1\%+2d)$; Earth resistance $\pm(2\%+2d)$ or $\pm 0.1\Omega$, which is greater.
- Battery: AA(1.5V)x6. (Not Included)
- Size: 163x100x50mm.

MT-3266

- 3 1/2 digits 1999 counts.
- 0.8% best accuracy.
- Portable and simple one-hand operation.
- Extra function: data hold, low battery indication.
- Max. jaw opening: max. 50mm.



DCV	1,000V $\pm(0.8\%+2d)$
ACV	750V $\pm(1.2\%+4d)$
ACA	200/1,000A $\pm(3.0\%+5d)$
Resistance	200Ω $\pm(1.0\%+3d)$, 20kΩ $\pm(1.0\%+1d)$
Continuity with beeper	Y
Power Source	NEDA1604/6F22 (9V) x 1pcs(Not included)
Size	230 x 70 x 37 mm
Individual package	Double blister