## **FHT-400U**

- Split hydraulic crimping head can work with hydraulic pump. It is suit for crimping big size of lugs.
- It is suitable for outside and inside project of the distributor house, the special tools for all kinds of connecting and building over head cable.

Crimping range:	Cu 16-400 mm <sup>2</sup>
65 53	(Common Systems) - By Anna Common State (Common Systems Common Sys
Crimping force:	120KN
Working pressure:	700bar.Max
Stroke:	20mm
Weight:	approx.3.9kg
Package:	Steel case
ACCESSORIES:	
Crimping dies:	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400 mm <sup>2</sup>
Sealing O-ring:	one set



## SYK-8B

- The finished distributor, on-off case and plate can change the specificational any time.
- We can make the tools according to customer's requirment, quick delivery.
- When order rectangle and square tools, please measure the correct dimension.

Punching range:	Φ22.5- φ 61.5 mm in the 3.5 mm mild steel.
Punching force:	100KN
Stroke:	25mm
Weight:	5.6kg
Package:	Steel case
Weight of the box:	3.0kgs
ACCECCODIEC	<u>.</u>



## ACCESSORIES:

Round Knockout punches Type D: 22.5, 28.3, 34.6, 43.2, 61.5 mm

7/16"x3/4" Draw Stud:1pc

3/4"x3/4" Draw Stud:1pc

Spacer:1pc Sealing kit:1set

Plastic box:1pc