

MT-2017/ MT-2007N

DCV	0.1/2.5/10/50/250V $\pm 3.0\%$ FSD, 1000V $\pm 4.0\%$ FSD	
Null DCV	DC ± 5 V, ± 25 V $\pm 5.0\%$ FSD	
ACV	10/50/250V $\pm 4.0\%$ FSD, 1000V $\pm 5.0\%$ FSD	
DCA	50 μ .2.5m/25m/250mA $\pm 3.0\%$ FSD, 10A $\pm 4.0\%$ FSD	
Resistance	x1(0.2~2k Ω)/x10(2~20k Ω)/ x100(20~200k Ω)/ x1k(200~2M Ω)/ x10k Ω (2k~20M Ω) $\pm 4.0\%$ ARC of scale length.	
Capacitance	C(Rx1k): 2000 μ F(Approx.)Max	
Battery Check	1.5V/9V	
Transistor check	Yes	
Diode & LED test	Yes	
Continuity with beeper	Yes	
Front panel controls	Range selector switch with "OFF" position, 0 Ω adjust knob.	
Battery	1.5V AAA x 2 and 9V(NEDA1604) x 1	
Size	171 x 108 x 37mm	
Individual Packing	Color box	

MT-3109

• 3 3/4 digits 3999 counts. • 1.0% best accuracy. • Auto range. • Overload protection. • Extra function: duty cycle, relative reference, data hold, sleep mode, auto power off, low battery indication. • Jaw opening size: max. 30		
Digits	3 3/4 digits 3999 counts	
DCV	400m $\pm (1.0\%+3d)$, 4/40/400V $\pm (1.0\%+1d)$, 600V $\pm (1.0\%+5d)$	
ACV	4/40/400V $\pm (1.2\%+5d)$, 600v $\pm (1.5\%+5d)$	
DCA	40A $\pm (2.5\%+5d)$, 400A $\pm (2.5\%+3d)$	
Resistance	400 Ω $\pm (1.2\%+5d)$, 4k/40k/400k Ω $\pm (1.0\%+5d)$, 4M Ω $\pm (1.2\%+5d)$, 40M Ω $\pm (1.5\%+5d)$	
Frequency	10/100/1k/10k/100k/1MHz $\pm (0.1\%+5d)$, 10MHz (For reference only.)	
Capacitance	40n/400n/4 μ /40 μ F $\pm (5.0\%+10d)$, 100 μ F $\pm (6.0\%+10d)$	
Extra function	duty cycle, relative reference, data hold, sleep mode, auto power off, low battery indication.	
Power Source	AAA(1.5V) x 3 pcs (Not included)	
Size	203 x 68 x 33 mm	
Accessories	Test lead and alligator clips	

8PK-ST1520



- 3 1/2 digit 1999 counts.
- Capable of measuring earth voltage.
- 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test.
- Extra function: data hold, auto power off, low battery, over range indication.
- Safety standard: IEC-1010(EN61010), installation Category III.
- Measurement: Earth Resistance by constant current.
- System: Invertor.820Hz, 2mA approx.
- Earth Voltage: 0~200V AC, 40~500Hz.
- Earth Resistance Range(Resolution): 0~20Ω(0.01Ω); 0~200Ω(0.4Ω), 0~2000Ω(1.0Ω).
- Accuracy: Earth voltage $\pm(1\%+2d)$; Earth resistance $\pm(2\%+2d)$ or $\pm 0.1\Omega$, which is greater.
- Battery: AA(1.5V)x6. (Not Included)
- Size: 163x100x50mm.

MT-3266

- 3 1/2 digits 1999 counts.
- 0.8% best accuracy.
- Portable and simple one-hand operation.
- Extra function: data hold, low battery indication.
- Max. jaw opening: max. 50mm.



DCV	1,000V $\pm(0.8\%+2d)$
ACV	750V $\pm(1.2\%+4d)$
ACA	200/1,000A $\pm(3.0\%+5d)$
Resistance	200Ω $\pm(1.0\%+3d)$, 20kΩ $\pm(1.0\%+1d)$
Continuity with beeper	Y
Power Source	NEDA1604/6F22 (9V) x 1pcs(Not included)
Size	230 x 70 x 37 mm
Individual package	Double blister